



# Diesel Compact Three phase BG600

|              | Prime      | Standby    |
|--------------|------------|------------|
| Genset model | DN3-BG600P | DN3-BG600S |
| 400V, 50Hz   | 550kVA     | 600kVA     |
|              | 440kW      | 480kW      |
| 440V, 60Hz   | 537.5kVA   | 593.8kVA   |
|              | 430kW      | 475kW      |

Ratings at 0.8 pf

**Prime:**

This rating is for the supply of continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation on the annual hours of operation and 10% overload power can be supplied for one hour in twelve hours.

**Standby:**

This rating is for the supply of continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted.



|                     |                 |                       |
|---------------------|-----------------|-----------------------|
| Engine model        | Scania          | DC16-44A (spec 10-27) |
| Number of cylinders | V8              |                       |
| Cubic capacity      | litre (cu inch) | 15.6 (952)            |
| Aspiration          | Turbocharged    |                       |
| Alternator          | Newage Stamford |                       |



Genset photograph may include optional extras

| Frequency                              |                            | 50Hz          | 60Hz          |
|--|----------------------------|---------------|---------------|
| Engine speed                           | rpm                        | 1,500         | 1,800         |
| Fuel tank capacity                     | litre (USgal)              | 820 (216.6)   | 820 (216.6)   |
| Fuel consumption at full rating:       | litre /h (USgal /h)        | 110.3 (29.14) | 110.9 (29.3)  |
| Prime                                  |                            |               |               |
| Standby                                | litre /h (USgal /h)        | 120.6 (31.86) | 120.6 (31.86) |
| Heat rejection to exhaust system (max) | kW (BTU /min)              | 382 (21,742)  | 376 (21,400)  |
| Heat rejection to cooling system (max) | kW (BTU /min)              | 196 (11,115)  | 197 (11,212)  |
| Total radiated heat (max)              | kW (BTU /min)              | 43 (2,447)    | 40 (2,277)    |
| Exhaust temperature (max)              | deg C (deg F)              | 530 (986)     | 471 (880)     |
| Radiator cooling air flow              | cu m /min (cfm)            | 588 (20,785)  | 510 (18,011)  |
| with max restriction                   | mm (inch) H <sub>2</sub> O | 20 (0.80)     | 20 (0.80)     |
| Combustion air flow (max)              | cu m /min (cfm)            | 33.3 (1,176)  | 38.3 (1,353)  |
| Exhaust gas flow (max)                 | cu m /min (cfm)            | 92.1 (3,253)  | 105.3 (3,719) |
| with max allowable back pressure       | mm (inch) H <sub>2</sub> O | 500 (19.7)    | 500 (19.7)    |


Note: Standard reference conditions: 25°C (77°F) air inlet temperature, 152.4m (500ft) above sea level, 60% relative humidity. All engine performance data based on the above mentioned maximum continuous ratings. Fuel consumption data at full load for diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, class A2.





# Diesel Compact Three phase BG600

| Dimensions:                       |           |               |
|-----------------------------------|-----------|---------------|
| Length (A)                        | mm (inch) | 3,710 (146.1) |
| Width (B)                         | mm (inch) | 1,167 (45.9)  |
| Height (C)                        | mm (inch) | 2,113 (83.2)  |
| Max longitudinal projection (D)   | mm (inch) | NA            |
| Max width projection per side (E) | mm (inch) | NA            |
| Maximum height total (F)          | mm (inch) | NA            |



| Weights:                               |         |               |
|--|---------|---------------|
| Dry weight (with lube oil)             | kg (lb) | 3,720 (8,201) |
| Wet weight (with lube oil and coolant) | kg (lb) | 3,780 (8,333) |

| Sound pressure levels: |       | 50Hz    | 60Hz    |
|------------------------|-------|---------|---------|
|                        |       | 1500rpm | 1800rpm |
| 15m, 75% load          | dB(A) | TBA     | TBA     |
| 15m, 100% load         | dB(A) | TBA     | TBA     |
| 7m, 75% load           | dB(A) | TBA     | TBA     |
| 7m, 100% load          | dB(A) | TBA     | TBA     |
| 1m, 75% load           | dB(A) | TBA     | TBA     |
| 1m, 100% load          | dB(A) | TBA     | TBA     |

In line with our policy of continuous development, we reserve the right to change specification without notice

DN3-BG600 - DS-707-0311



**Burtonwood**<sup>TM</sup>  
Generator & Switchgear Services

Tel: +44 (0) 1744 814444  
Fax: +44 (0) 1744 814455  
Email: sales@burtonwoodgroup.com  
Web: www.burtonwoodgroup.com

Unit 2, St Michaels Road  
St Helens  
Merseyside  
WA9 4WZ